https://trungtamthuoc.com/

Status: Currently Official on 13-Feb-2025
Official Date: Official as of 01-Aug-2022
Document Type: USP Monographs
DocId: GUID-73A32F56-3220-45CD-A416-D3FC85416682_3_en-US
DOI: https://doi.org/10.31003/USPNF_M6472_03_01
DOI Ref: uzd20

© 2025 USPC Do not distribute

Colloidal Activated Attapulgite

DEFINITION

Colloidal Activated Attapulgite is a purified native magnesium aluminum silicate.

IDENTIFICATION

• A. X-Ray Powder Diffraction (941)

Sample: 2 g

Analysis: Add the *Sample* in small portions to 100 mL of <u>water</u>, with vigorous agitation. Allow to stand for at least 12 h to ensure complete hydration. Place 2 mL of the resulting mixture on a suitable glass slide, and allow to air-dry at room temperature to produce a uniform film. Place the slide in a vacuum desiccator over a free surface of <u>ethylene glycol</u>. Evacuate the desiccator, and close the stopcock so that the ethylene glycol saturates the desiccator chamber. Allow to stand for 12 h. Record the X-ray diffraction pattern and calculate the *d* values.

Acceptance criteria: Several peaks are observed; the characteristic peak corresponds to a d value between 10.3 and 10.7 Å.

IMPURITIES

• Loss on Ignition (733)

Analysis: Ignite at 1000° for 1 h. **Acceptance criteria:** 17.0%–27.0%

Delete the following:

▲• Arsenic and Lead

Sample solution: 50 mg/mL of Colloidal Activated Attapulgite prepared as follows. To 5.0 g add 50 mL of 1 N <u>nitric acid</u>, and boil for 30 min, adding 1 N <u>nitric acid</u> at times to maintain the volume. Filter into a 100-mL volumetric flask, wash the filter with <u>water</u>, and dilute the combined filtrate and washings with <u>water</u> to volume.

Instrumental conditions

(See <u>Atomic Absorption Spectroscopy (852)</u>)

Mode: Atomic absorption spectrophotometry equipped with graphite furnace

Atomization source: Graphite furnace, as directed by the manufacturer of the instrument used

Analytical wavelength Arsenic: 189.0 nm Lead: 283.3 nm

Analysis

Sample: Sample solution

Determine the arsenic or lead in the solution against corresponding standard

Acceptance criteria
Arsenic: NMT 2 ppm

Lead: NMT 0.001% (USP 1-Aug-2022)

• Acid-Soluble Matter Sample: 2.0 g

Analysis: Boil the *Sample* with 100 mL of 0.2 N <u>hydrochloric acid</u> for 5 min, and cool. Add <u>water</u> to adjust the volume to 100 mL, and filter. Evaporate 50 mL of the filtrate so obtained to dryness. Ignite the residue at 600°.

Acceptance criteria: NMT 0.15~g~(15%)

• CARBONATE
Sample: 1.0 q

Analysis: Mix the Sample with 15 mL of 0.5 N sulfuric acid.

Acceptance criteria: No effervescence occurs.

• VOLATILE MATTER

Analysis: Ignite at 600° for 1 h.

Acceptance criteria: 7.5%-12.5% on the dried basis

SPECIFIC TESTS

• **PH** (791)

https://trungtamthuoc.com/

Sample solution: 100 mg/mL of Colloidal Activated Attapulgite prepared as follows. Disperse 1.0 g of Colloidal Activated Attapulgite in 10 mL of <u>carbon dioxide-free water</u>, and mix.

Acceptance criteria: 7.0-9.5

• Loss on Drying (731)

Analysis: Dry at 105° to constant weight. **Acceptance criteria:** 5.0%–17.0%

• Powder Fineness Sample: 50 g

Analysis: Add the Sample to 450 mL of water containing 5 g of sodium pyrophosphate, and stir for 10 min. Pour the resulting dispersion slowly through a No. 325 standard sieve (see Particle Size Distribution Estimation by Analytical Sieving (786)), and carefully wash the residue until clean. Dry the residue at 105° to constant weight.

Acceptance criteria: The dry weight of the residue is NMT 0.30% of the weight of the sample taken.

• ADSORPTIVE CAPACITY

Barium chloride solution: 20 mg/mL of <u>barium chloride</u> in <u>water</u> **Methylene blue solution:** 1 mg/mL of <u>methylene blue</u> in <u>water</u> **Standard solution:** 1.5 μ g/mL of <u>methylene blue</u> in <u>water</u>

Sample solution: Prepare a solution of 100 mg/mL of Colloidal Activated Attapulgite in water. To 10 mL of this solution add 80 mL of Methylene blue solution, and shake. Add 10 mL of Barium chloride solution, and shake. Allow to stand for 15 min. Transfer 40 mL of the supernatant to a 50-mL centrifuge tube, and centrifuge. To 5 mL of the clear supernatant add 495 mL of water, and mix.

Analysis

Samples: Standard solution and Sample solution

Compare the color of the Sample solution to that of the Standard solution.

Acceptance criteria: The color of the Sample solution is not deeper than that of the Standard solution.

• MICROBIAL ENUMERATION TESTS (61) and TESTS FOR SPECIFIED MICROORGANISMS (62): It meets the requirements of the test for absence of Escherichia coli.

ADDITIONAL REQUIREMENTS

• PACKAGING AND STORAGE: Preserve in well-closed containers.

Auxiliary Information - Please check for your question in the FAQs before contacting USP.

Topic/Question	Contact	Expert Committee
COLLOIDAL ACTIVATED ATTAPULGITE	Documentary Standards Support	SM32020 Small Molecules 3

Chromatographic Database Information: Chromatographic Database

Most Recently Appeared In: Pharmacopeial Forum: Volume No. 47(2)

Current DocID: GUID-73A32F56-3220-45CD-A416-D3FC85416682_3_en-US

DOI: https://doi.org/10.31003/USPNF_M6472_03_01

DOI ref: uzd20