

Status: Currently Official on 16-Feb-2025
Official Date: Official as of 01-May-2021
Document Type: USP Monographs
DocId: GUID-379C543A-4FCE-4A2A-9C11-8BEEDA760718_4_en-US
DOI: https://doi.org/10.31003/USPNF_M77670_04_01
DOI Ref: z1670

© 2025 USPC
Do not distribute

Sorbitol Solution

DEFINITION

Sorbitol Solution is an aqueous solution containing NLT 64.0% of *D*-sorbitol ($C_6H_{14}O_6$). The amounts of total sugars, other polyhydric alcohols, and any hexitol anhydrides, if detected, are not included in the requirements nor in the calculated amount as stated in [General Notices](#), [5.60.10 Other Impurities in USP and NF Articles](#).

IDENTIFICATION

• A.

Sample solution: Dissolve 1.4 g of Sorbitol Solution in 75 mL of [water](#).

Analysis: Transfer 3 mL of the *Sample solution* to a 15-cm test tube. Add 3 mL of a freshly prepared solution of [catechol](#) (1 in 10), and mix. Add 6 mL of [sulfuric acid](#), mix again, and gently heat the tube in a flame for 30 s.

Acceptance criteria: A deep pink or wine-red color appears.

• B. The retention time of the major peak of the *Sample solution* corresponds to that of the *Standard solution*, as obtained in the [Assay](#).

• C. **LIMIT OF DIETHYLENE GLYCOL AND ETHYLENE GLYCOL**

Diluent: [Acetone](#) and [water](#) (96:4)

Standard solution: 0.08 mg/mL of [USP Diethylene Glycol RS](#) and 0.08 mg/mL of [USP Ethylene Glycol RS](#) in *Diluent*

Sample solution: Transfer 2.0 g of Sorbitol Solution to a 25-mL volumetric flask. Add 1.0 mL of *Diluent* to the flask, and mix on a vortex mixer for 3 min. Add the remaining *Diluent* to the flask to volume in 3 equal portions. Mix on a vortex mixer for about 3 min after each addition of *Diluent*. Pass a portion of the supernatant layer obtained through a 0.45- μ m nylon filter. Discard the first 2 mL of the filtrate, and collect the rest of the filtrate for analysis. [NOTE—Acetone is used to precipitate sorbitol.]

Chromatographic system

(See [Chromatography \(621\), System Suitability](#).)

Mode: GC

Detector: Flame ionization

Column: 0.32-mm \times 15-m fused-silica capillary column; 0.25- μ m layer of phase [G46](#)

Temperatures

Detector: 300°

Injection port: 240°

Column: See [Table 1](#).

Table 1

Initial Temperature (°)	Temperature Ramp (°/min)	Final Temperature (°)	Hold Time at Final Temperature (min)
70	—	70	2
70	50	300	5

Carrier gas: Helium

Flow rate: 3.0 mL/min

Injection volume: 1.0 μ L

Injection type: Split, split ratio 10:1. [NOTE—A split liner, deactivated with glass wool, is used.]

System suitability

Sample: *Standard solution*

[NOTE—Diethylene glycol elutes after ethylene glycol.]

Suitability requirements

Resolution: NLT 30 between ethylene glycol and diethylene glycol

Analysis

Samples: Standard solution and Sample solution

Based on the Standard solution, identify the peaks of ethylene glycol and diethylene glycol. Compare peak areas of ethylene glycol and diethylene glycol in the Standard solution and the Sample solution.

Acceptance criteria

Diethylene glycol: The peak area of diethylene glycol in the Sample solution is NMT the peak area of diethylene glycol in the Standard solution, corresponding to NMT 0.10% of diethylene glycol in Sorbitol Solution.

Ethylene glycol: The peak area of ethylene glycol in the Sample solution is NMT the peak area of ethylene glycol in the Standard solution, corresponding to NMT 0.10% of ethylene glycol in Sorbitol Solution.

ASSAY

• PROCEDURE

Mobile phase: [Water](#)

System suitability solution: 4.8 mg/g of mannitol and 4.8 mg/g of [USP Sorbitol RS](#) in [water](#)

Standard solution: 4.8 mg/g of [USP Sorbitol RS](#) in [water](#)

Sample solution: 6.0 mg/g of Sorbitol Solution in [water](#)

Chromatographic system

(See [Chromatography \(621\), System Suitability](#).)

Mode: LC

Detector: Refractive index

Column: 7.8-mm × 10-cm; packing [L34](#)

Temperatures

Detector: 35°

Column: 50 ± 2°

Flow rate: 0.7 mL/min

Injection volume: 10 µL

System suitability

Samples: System suitability solution and Standard solution

[NOTE—The relative retention times for mannitol and sorbitol are 0.6 and 1.0, respectively.]

Suitability requirements

Resolution: NLT 2.0 between sorbitol and mannitol, System suitability solution

Relative standard deviation: NMT 2.0% for sorbitol, Standard solution

Analysis

Samples: Standard solution and Sample solution

Calculate the percentage of D-sorbitol ($C_6H_{14}O_6$) in the portion of Sorbitol Solution taken:

$$\text{Result} = (r_U/r_S) \times (C_S/C_U) \times 100$$

r_U = peak response of sorbitol from the Sample solution

r_S = peak response of sorbitol from the Standard solution

C_S = concentration of [USP Sorbitol RS](#) in the Standard solution (mg/g)

C_U = concentration of Sorbitol Solution in the Sample solution (mg/g)

Acceptance criteria: NLT 64.0%

IMPURITIES

• [RESIDUE ON IGNITION \(281\)](#): NMT 0.1%, calculated on the anhydrous basis, determined on a 2-g portion

Change to read:

• [LIMIT OF NICKEL](#)

▲[NOTE—When water is specified as the diluent, use deionized ultra-filtered water. Use of glass volumetric flasks is discouraged.]

Digest solution: Add 360 mL of [hydrochloric acid, ultratrace](#), and 240 mL of [nitric acid, ultratrace](#), to 1200 mL of water.

Blank solution: Add 40 mL of [nitric acid, ultratrace](#), to a 2000-mL volumetric flask, dilute with water to volume, and mix well.

Internal standard solution: Transfer 2.0 mL of solution containing 1000 mg/L of yttrium¹ to a 1000-mL volumetric flask, dilute with *Blank solution* to volume, and mix well. The *Internal standard solution* contains 2 µg/mL of yttrium. [NOTE—The concentration of the *Internal standard solution* can be adjusted if a high number of signal counts from the *Internal standard solution* causes an artifact.]

Standard stock solution: [NOTE—Prepare this solution fresh every 2 months.] Quantitatively dilute an accurately measured volume of the solution containing 1000 mg/L of nickel² with *Blank solution* to obtain a solution containing 10 µg/mL of nickel.

Standard nickel solution A: [NOTE—Prepare this solution fresh weekly.] Pipet 1.0 mL of *Standard stock solution* into a 200-mL volumetric flask. Dilute the content in the flask with *Blank solution* to volume, and mix well. This solution contains 50 ng/mL of nickel.

Standard nickel solution B: [NOTE—Prepare this solution fresh weekly.] Pipet 2.0 mL of *Standard stock solution* into a 200-mL volumetric flask. Dilute the content in the flask with *Blank solution* to volume, and mix well. This solution contains 100 ng/mL of nickel.

Standard nickel solution C: [NOTE—Prepare this solution fresh weekly.] Pipet 4.0 mL of *Standard stock solution* into a 200-mL volumetric flask. Dilute the content in the flask with *Blank solution* to volume, and mix well. This solution contains 200 ng/mL of nickel.

Sample solution: Transfer a quantity of Sorbitol Solution, equivalent to 10.0 g on the anhydrous basis, into a 125-mL conical flask. Add 40 mL of *Digest solution*, and place on a hot plate. Heat the solution for about 20 min, being careful to prevent the solution from boiling over. Pull the sample off the hot plate just before it turns a dark caramel color. [NOTE—Do not overburn the sample.] Transfer the flask's contents into a clean, dry, 50-mL volumetric flask with washings of *Blank solution*. Dilute with *Blank solution* to volume. Filter the sample into a 15-mL centrifuge tube, using a 10-mL disposable syringe fitted with a syringe filter of 0.45-µm pore size.

Instrumental conditions

(See [Plasma Spectrochemistry \(730\)](#).)

Mode: ICP–OES

Emission wavelengths: 232.005 nm for nickel and 371.029 nm for yttrium. Set the sample read time and other instrument parameters as appropriate or as recommended by the instrument manufacturer.

System suitability

Samples: *Blank solution*, *Standard nickel solution A*, *Standard nickel solution B*, and *Standard nickel solution C*

Suitability requirements

[NOTE—Instrument performance must be verified to conform to the manufacturer's specifications for resolution and sensitivity. Before analyzing samples, the instrument must pass a suitable performance check.]

Correlation coefficient: NLT 0.999, determined from the *Calibration curve* constructed in the *Analysis*

Analysis

Samples: *Blank solution*, *Standard nickel solution A*, *Standard nickel solution B*, and *Standard nickel solution C*, and *Sample solution*

[NOTE—The following analysis is described for one type of ICP–OES instruments. If a different ICP–OES instrument is used, follow the instrument manufacturer's recommendations for operation.]

Take 3 replicate scans with the integration set as recommended by the instrument manufacturer. Follow the instrument manufacturer's recommendations for delivering the sample. Add the *Internal standard solution* in-line via a mixing block between the sample probe and the spray chamber. Flush the samples through the system before analysis. Program a read delay into the sampling routine to allow for fluid flow equilibration after the high-speed flush, before the first analytical read of the sample. Between samples, wash the pumping system by flushing the *Blank solution*.

Calibration curve: Generate the calibration curve using the *Blank solution*, *Standard nickel solution A*, *Standard nickel solution B*, and *Standard nickel solution C* as follows. Scan the *Internal standard solution* while running the *Blank solution* to measure the intensity of the yttrium emission. Hold this value constant throughout the remainder of the test. Separately scan the *Blank solution*, *Standard nickel solution A*, *Standard nickel solution B*, and *Standard nickel solution C* for nickel and yttrium. [NOTE—Add the *Internal standard solution* via an in-line mixing chamber.] Normalize the yttrium intensity to the value of the *Internal standard solution*. Apply this normalization factor to the nickel intensity, which is then referred to as the corrected nickel intensity. Construct a calibration curve by plotting the corrected nickel intensity versus the known concentrations, in ng/mL, of nickel.

Similarly, analyze the *Sample solution*. Plot the intensity of the emission of the *Sample solution* on the calibration curve. Determine the concentration of nickel (C), in ng/mL, in the *Sample solution* through the calibration curve.

Calculate the content, in µg/g, of nickel in the solid portion of Sorbitol Solution taken:

$$\text{Result} = (F \times V \times C) / W$$

F = conversion factor, 10^{-3} µg/ng (ng to µg)

V = volume of the *Sample solution*, 50 mL

C = concentration of nickel in the *Sample solution* (ng/mL)

W = weight of Sorbitol Solution calculated on the anhydrous basis (g)

Acceptance criteria: NMT 1 µg/g▲ (USP 1-May-2021)

• REDUCING SUGARS

[NOTE—The amount determined in this test is not included in the calculated amount as requested in [General Notices, 5.60.10 Other Impurities in USP and NF Articles.](#)]

Sample: Equivalent to 3.3 g of sorbitol on the anhydrous basis from Sorbitol Solution

Analysis: To the *Sample*, add 3 mL of [water](#), 20.0 mL of [cupric citrate TS](#), and a few glass beads. Heat so that boiling begins after 4 min, and maintain boiling for 3 min. Cool rapidly and add 40 mL of [diluted acetic acid](#), 60 mL of [water](#), and 20.0 mL of [0.05 N iodine VS](#). With continuous shaking, add 25 mL of a mixture of 6 mL of hydrochloric acid and 94 mL of water. When the precipitate has dissolved, titrate the excess of iodine with [0.05 N sodium thiosulfate VS](#) using 2 mL of [starch TS](#), added toward the end of the titration, as an indicator.

Acceptance criteria: NLT 12.8 mL of the 0.05 N sodium thiosulfate VS is required, corresponding to NMT 0.3% of reducing sugars, on the anhydrous basis, as glucose.

SPECIFIC TESTS**Delete the following:**

- ▲ [pH \(791\)](#): 5.0–7.5, in a 14% (w/w) solution of Sorbitol Solution in carbon dioxide-free water▲ (USP 1-May-2021)

Add the following:**▲ CONDUCTIVITY**

Sample: Sorbitol Solution

Analysis: Calibrate the conductivity meter using a 10 $\mu\text{S}/\text{cm}$ certified reference standard. Measure the undiluted *Sample* while gently stirring with a magnetic stirrer.

Acceptance criteria: NMT 10 $\mu\text{S}/\text{cm}$ ▲ (USP 1-May-2021)

- [WATER DETERMINATION \(921\), Method I](#): 28.5%–31.5%

ADDITIONAL REQUIREMENTS

- **PACKAGING AND STORAGE:** Preserve in well-closed containers. No storage requirements are specified.

• USP REFERENCE STANDARDS (11).

[USP Diethylene Glycol RS](#)

[USP Ethylene Glycol RS](#)

[USP Sorbitol RS](#)

¹ Yttrium ICP standard solutions are commercially available. A suitable yttrium ICP standard is available from LGC (www.lgcstandards.com) or Millipore Sigma (www.sigmapel.com).

² Nickel ICP standard solutions are commercially available. A suitable nickel ICP standard is available from LGC (www.lgcstandards.com) or Millipore Sigma (www.sigmapel.com).

Auxiliary Information - Please [check for your question in the FAQs](#) before contacting USP.

Topic/Question	Contact	Expert Committee
SORBITOL SOLUTION	Documentary Standards Support	SE2020 Simple Excipients
REFERENCE STANDARD SUPPORT	RS Technical Services RSTECH@usp.org	SE2020 Simple Excipients

Chromatographic Database Information: [Chromatographic Database](#)

Most Recently Appeared In:

Pharmacopeial Forum: Volume No. 50(2)

Current DocID: GUID-379C543A-4FCE-4A2A-9C11-8BEEDA760718_4_en-US

DOI: https://doi.org/10.31003/USPNF_M77670_04_01

DOI ref: [z1670](#)